


## OPTIONAL ACCESSORIES

Variety of Accessories and Replacement Parts




### 6 mm Camera (0.24")

Video resolution of 720 x 480 dpi with 4 LED lights mounted on the camera head with 60° viewing angle, inside of a rugged stainless steel enclosure.



### 12 mm Camera (0.47")

Video resolution of 720 x 480 dpi with a 512 Hz sonde and 6 LED lights mounted on the camera head with 65° viewing angle, inside of a stainless steel enclosure.




### 17 mm Camera (0.67")

Video resolution of 720 x 480 dpi with a 512 Hz sonde and 6 LED lights mounted on the camera head with 120° viewing angle, inside of a stainless steel enclosure.



### 23 mm Camera (0.90")

Video resolution of 720 x 480 dpi with a 512 Hz sonde and 12 LED lights mounted on the camera head with 120° viewing angle, inside of a stainless steel enclosure.



### 28 mm Camera \*Self-Leveling (1.1")

Video resolution of 720 x 480 dpi with a 512 Hz sonde and 12 LED lights mounted on the self-leveling camera head with 120° viewing angle, inside of a rugged stainless steel enclosure.



### 38 mm Camera \*Self-Leveling (1.5")

Video resolution of 720 x 480 dpi with a 512 Hz sonde and 12 LED lights mounted on the self-leveling camera head with 90° viewing angle, inside of a rugged stainless steel enclosure.



### 30m - 40m - 50m Wheels

98.3'-131'-164' wheels. Metal frame enclosure with a fiberglass rod of 0.19" (5 mm) diameter.



### 60m - 80m Wheels

197'-263' wheels. Metal frame enclosure with carrying handle. Fiberglass rod of 0.27" (7 mm) diameter. Meter counter and handle brake.



### 60m Wheel

197' wheel. Metal frame enclosure with carrying handle, big rolling wheels for extra mobility and easy transport. Featuring a 0.35" (9 mm) diameter fiberglass rod.



### 512 Hz Sondes

Standard sewer sondes attach to any SSI cable wheel. Require (2) A76 batteries (included).  
Regular: 2.125" x 0.875"  
Mini: 1.875" x 0.625"




### Camera Skids

Variety of sizes for the different camera heads. Attach to the camera for added protection and to center the video image on the screen.



### Universal Skid

Spring loaded, adjustable legs for different pipe sizes from 5.5" to 15.7". Rolling wheels provide easier mobility inside of the inspected pipes.



### LED light

Convenient LED rim powered with a rechargeable waterproof battery, to be used with the Universal Skid. It provides an extra illumination option for increased visibility.

