PRECISION TESTING LABORATORIES, INC.



313 Hill Avenue, NASHVILLE TN 37210-4711 PHONE 615-254-3401 FAX 615-254-3488 www.precisiontesting.com

 Laboratory Report No.
 12169
 Page 1 of 1

 20-Jun-12
 Page 1 of 1

ACP International 521 N. Great Southwest Pkwy. Arlington, TX 76011

Cc: n/a PO#: n/a

Item: One (1) sample of graphics materials

Identification: Concrete Graphics® CGB42150

Purpose: Slip Resistance, ASTM F 1677-05

Rubber Property, Durometer Hardness, ASTM D 2240-05

Test		Specimen Results				Average	Stdev
	Unit of Measure						
Slip Resistance							
STM F 1677-05, Mar	<u>k II</u>						
leolite Fineline - J &	M						
leel							
		<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>		
	Tile # 1	_	_	_	_		
	Dry	0.55	0.56	0.55	0.56	0.56	0.01
	Wet	0.59	0.58	0.57	0.57	0.58	0.01
		0.00	0.00	0.01	5.5.	0.00	0.0.
	Tile # 2						
	Dry	0.60	0.62	0.60	0.61	0.61	0.01
	Wet	0.67	0.61	0.61	0.64	0.63	0.03
	WCt	0.07	0.01	0.01	0.04	0.00	0.00
	Tile # 3						
	Dry	0.64	0.68	0.68	0.69	0.67	0.02
	Wet	0.68	0.69	0.67	0.65	0.67	0.02
	VVCI	0.00	0.03	0.07	0.03	0.07	0.02
					Dry Average (3 tiles)	0.61	n/a
					Wet Average (3 tiles)	0.63	
Nin Danistanaa Taat	Danamintian				vvei Average (3 tiles)	0.63	n/a
lip Resistance, Test	Description						
ry =	Dm						
Vet =		Dry 25 mls distilled water					
vet =	25 mis distilled	23 mis distilled water					
uhhan Duamantii Diii	t						
Rubber Property, Du	ometer Hardness						
ASTM D 2240-05	T A						
Shore Instrument Du	rometer Type A						
s received							
N	Et - Finalina LOAA	00	00	00	00 00	00	
Neo	lite Fineline - J & M	88	90	89	88 90	89	1
Shore Instrument Di	ırometer Tyne "A" ser	ıal # 88533 ii	itilizing a Shore T	vne 1 operating	stand with a constant contact pr	essure	

I certify that the above tests under my supervision were performed in accordance with the specification test requirements and that the reported results are true, valid and applicable to the samples tested. I further certify that these samples were the only samples tested from the lot of end items identified above.

controlled atmosphere of 72° F and 50% RH. Meter calibrations are conducted prior to test.

Signed: Suzame Tuspanen. Suzame Piispanen, VP Operations

Don G. Roney, Laboratory Manager

This report is limited to and related only to the particular instrument, material or other subject to which it refers. These test results can not be compared to results obtained using different methods or under different conditions. No representation is made that similar articles will be of like quality. Neither Precision Testing Laboratories, Inc (hereinafter "Precision Testing") nor their officers, directors, managers or employees, shall be responsible for any loss or damage resulting directly or indirectly from any failure, error or omission in testing, or in the reporting of test results. Precision Testing has no controls, and assumes no responsibility for the tested product's functionality or use. Precision Testing's liability shall not exceed the fees paid for the testing reflected on this report. Precision Testing observes and maintains client confidentiality, and limits reproduction of this report, except in full, without prior approval of Precision Testing.