

Maintaining beautiful pool water
has never been this easy.



Introducing the
VANTAGE® ACF-250
Calcium Hypochlorite Tablet Feeder

- ✓ **SIMPLE:** easy to install, operate and service
- ✓ Safer than gas or liquid chlorine
- ✓ Treats pools up to 1,000,000 gallons
- ✓ NSF Certified
- ✓ Rugged design for trouble-free operation



AllChem Performance Products, LP
6010 NW First Place, Gainesville FL 32607
Phone: 352.333.7317 www.vantagewatercare.com



Vantage® ACF-250 Calcium Hypochlorite Feeder

Operating Specifications

Inlet Flow 2.0-3.5 gpm
Outlet Flow = Inlet Flow
Inlet Pressure 10 - 45 psig

Maximum Output (available Cl₂)

Pool: 200 Lbs. / Day (80°F) at 30 psig inlet pressure

Capacity: 250 lbs. Vantage® Calcium Hypochlorite Tablets

Operating Temperature: 40-104°F

Feeder Base 21" x 27"
Feeder Height 43.5"
Feeder weight (full) 320 lbs.
Feeder weight (empty) 70 lbs.
Tubing 5/8" O.D.

FOR SWIMMING POOL USE ONLY

Recommended Pool Size (US Gallons)
up to 1,000,000 gallons

More About the ACF-250 Calcium Hypochlorite Feeder

Easily installed and easy to service, the Vantage ACF-250 Calcium Hypochlorite Feeder is designed for the commercial pool operator's convenience. With a hopper that holds 250 pounds of Vantage® Calcium Hypochlorite Tablets, it can handle pools up to 1,000,000 gallons. What's more, it can easily be installed in tandem in order to provide less frequent filling of the feeder when used on larger pools. This design also provides many safety features for the operator.

Designed for use with electronic controllers, our feeder can deliver up to 200 lbs. of available chlorine per day (307 pounds of Vantage® Calcium Hypochlorite Tablets.)

Plumbing Installation

Install a separate pump and venturi system to supply the feeder with water and draw the chlorinated solution out of the feeder. Set the feeder in a location that is easy to fill. Use 5/8" tubing (supplied with unit) to connect to the water supply and venturi.

Electrical Installation

Simple plugin installation - no wiring necessary. Plug the chlorine feed solenoid directly into the plug from the electronic controller. Plug the inlet water solenoid valve directly into a 115V GFCI protected outlet.

Operation

1. Filling the ACF-250 is easy with a lift-off lid that can be secured with a locking bar and pin.
2. An innovative pull-out top allows you to watch the feeder operate without turning the feeder off. This feature also allows for quick inspection and cleaning of internal components.

Service

The ACF-250 was designed for easy service. Two removable panels on the top of the lower tank provide easy access to hose out the basin or remove and clean components. The scrubbing action of the rinse nozzle, combined with the smooth surfaces of the feeder will reduce scale buildup.

The tablet hopper is designed to be removed without tools, to facilitate full, easy access to the lower tank.

Solenoid valves are installed for easy removal and replacement. Mounting hardware and piping stays in place and the valves simply spin off