

inspiralR & FLOVAL

Introduction

Give your round ductwork increased thermal performance with Therma duct's InspiralR and Floval Duct Systems. These patent pending systems provide the increased air distribution efficiency of round and flat oval ductwork packaged in an extremely lightweight and high quality closed cell phenolic insulation. There's no need to insulate separately as all InspiralR and Floval Ductwork reach a minimum of R-6 Insulated value!

Standard Features

- High R-value - R-6 Standard
 - Low air leakage
 - Water resistant
 - Closed cell, zero fiber insulation
 - Low and medium pressure class
 - UL 181 Listed 10" Positive, 8" Negative Pressure Class
 - Low thermal expansion
 - LEED point eligible
 - 10 year limited warranty *
- * See warranty statement for full warranty details



Compare InspiralR to double wall metal ductwork to see if your current duct might be weighing you down

Duct Type	therma duct inspiralR	Double Wall Metal
Application	Indoor	Indoor
Size (ID)	22"	22"
Length (less coupling)	47.25"	47.25"
R-value	R-6	R-4
Insulation	Closed Cell Phenolic foam	Open Cell fiberglass
Interior Surface	Linear smooth	Non-linear, not smooth
Weight	11lbs 7.5oz	47lbs 9oz
Static Pressure	10" Positive, 8" Negative	10" (not a UL Listed Product)



Air Distribution Solved

InspiralR and Floval fittings are pre-fabricated and arrive to the jobsite with included coupling and drawband connections*. Talk to your local Therma duct representative to learn more about how our lightweight and efficient systems can save you time and money in your next installation.



**size and pressure class determine draw band connections*



HIGH EFFICIENCY AIR DISTRIBUTION

www.therma duct.com