

		MODEL	KFORCE R20 ROTARY ARM WRAPPER
SPECIFICATIONS		SPEED	20 RPM
		RATED LPH (BASED ON 8 WRAPS, 60 FPM CONVEYOR SPEED)	70
		LOAD SIZE MAX (L x W x H)	44" x 56" x 110" (FOR ADDITIONAL SIZES, KES REVIEW)
		LOAD SIZE MIN (L x W x H)	36" x 40" x 18" (FOR ADDITIONAL SIZES, KES REVIEW)
		FILM SIZE	20" TO 30" ROLL WIDTH
		HOLD DOWN	OPTIONAL
		PRESTRETCH	0-300%
		CORNERBOARD	OPTIONAL
		DRY WEIGHT (SHIPPING WEIGHT)	6600 LBS
		FILM CUT	QUICK CHANGE IMPULSE HOT WIRE
		C-A-M	OPTIONAL
		SAFETY	CATEGORY 3
		LOW FILM NOTIFICATION	STANDARD
		LUBRICATION	CENTRAL
MACHINE DESCRIPTION		ARM DRIVE	AB POWERFLEX 525 (2) HP 37" ROTEK GEAR BEARING
		FILM ELEVATOR	AB POWERFLEX 525 (1) HP SPRING TENSIONED CHAIN DRIVE
		PRESTRETCH	AB POWERFLEX 525 (1) HP POSITIVE CHAIN DRIVEN STRETCH ROLLERS
		FRAME	8" x 8" TUBE
		HOLD DOWN (OPTIONAL)	AB POWERFLEX 525 (1) HP SPRING TENSIONED CHAIN DRIVE
CONTROLS		ENCLOSURES	HOFFMAN
		PLC	AB LOGIX FAMILY
		HMI	AB PANELVIEW PLUS SERIES
		DISCONNECT	AB RIGHT HAND FLANGE STYLE
STANDARD COMPONENTS	MECH.	MOTORS	BALDOR
		GEARBOX	DODGE, TIGEAR
		VALVES	NUMATICS
	ELEC.	PHOTOEYES	EFFECTOR
		LIMIT SWITCHES	ALLAN BRADLEY
		SAFETY GATE SWITCHES	FORTRESS "T" GUARD