

OFF SEASON SERVICE WORKSHEET FOR COMMERCIAL MOWING EQUIPMENT

OWNER:	MODEL:	PURCHASE DATE:	SERIAL #:
--------	--------	----------------	-----------

SAFETY	TEST ALL SAFETY INTERLOCK FUNCTIONS	
LUBRICATE	GREASE ALL FITTINGS, OIL ALL CABLES	
FUEL SYSTEM	TREAT FUEL WITH FUEL STABILIZER – INSPECT FOR LEAKS `WE USE SEA FOAM` & K100	
TIRES	PROPER AIR PRESSURE ADJUSTMENT	
	INSPECT – FOR LEAKS – ADVISE OF REPLACEMENTS	
ADDITIONAL \$	SEAL TIRES WITH LIQUITUBE HD TIRE SEALANT. *Walker \$77. *Mid Z Rider \$90. *Stander \$54. *Walk Behind \$45.	
ENGINES	CHANGE ENGINE OIL AND FILTER, CHANGE AIR FILTER, CHANGE FUEL FILTER	
	CHANGE / GAP SPARK PLUGS	
	INSPECT FOR OIL SEAL LEAKS / HIGHER HOUR ENGINES WITH OBSERVED OIL LEAKS REQUIRE ENGINE REMOVAL OR PARTIAL DISMANTLING FOR PROPER CLEANING & OIL SEAL OR GASKET REPLACEMENT. <u>REQUIRED LABOR & PARTS EXPENSE ADDITIONAL</u>	
	CLEAN DEBRIS ACCUMULATION FROM CYLINDER HEAD COOLING FINS / VERTICAL SHAFT ENGINE REQUIRE REMOVAL OF ENGINE SHROUD TO EXPOSE CYLINDER HEAD COOLING FINS. HORIZONTAL SHAFT ENGINES – IN WALKER MOWERS – REMOVE BOTH INSPECTION PLATES ON ENGINE SHROUDS AND USE COMPRESSED AIR TO BLOW OUT CYLINDER HEAD COOLING FINS. *YOU SHOULD BE DOING THIS PROJECT EVERY 200 HOURS.	
	TACH ENGINE – ADJUST GOVERNOR TO PROPER RPM’S	
ADDITIONAL \$	KAWASAKI – ADJUST VALVES – RECOMMENDED YEARLY OR EVERY 300 HOURS	
ELECTRICAL	CHECK BATTERY – CLEAN TERMINALS, CHECK CHARGING (14 VOLTS AT FULL THROTTLE)	
	CHECK & CLEAN ALL ELECTRICAL CONNECTIONS AS NEEDED, AND APPLY “DIELECTRIC GREASE”	
HYDRO DRIVES	CHANGE OIL AND FILTERS AT MANUFACTURES RECOMMENDED INTERVAL	
	CHECK / TOP OFF GEAR AXLE DRIVES WITH GEAR OIL	
	CLEAN COOLING FINS – CHECK SYSTEMS FOR LEAKS	
DRIVE SYSTEMS	BELT INSPECTION & ADVISE	
	INSPECT ALL PULLEYS & ADVISE OF SEVERELY WORN / GROOVED OUT PULLEYS	
	ADJUST ELECTRIC BLADE CLUTCH WERE APPLICABLE	
	ADJUST STRAIGHT TRACKING AND NEUTRAL FUNCTIONS	
MOWER DECKS	INSPECT & ADVISE OF WORN SPINDLE BEARINGS, WORN IDLER PULLEYS AND BELTS	
	CHECK WALKER GEAR DRIVE SYSTEMS FOR PROPER GEAR LUBE LEVEL (AND FOR LEAKS)	
	SHARPEN AND BALANCE BLADES	
CLEAN	PRE-SOAP & HOT WASH EXTERIOR OF TRACTOR & UNDERSIDE OF MOWER DECK, COMPRESSED AIR CLEANING OF ENGINE & ENGINE COMPARTMENTS, APPLY `FLUID FILM TO UNDERSIDE OF MOWER DECK	

Notes: _____

REFER TO OWNER’S MANUAL FOR SPECIFIC INSTRUCTION AND SAFETY PRECAUTIONS

*Emmett Equipment Company * Richfield, OH *800-659-5520

www.emmettequipment.com

OFF SEASON SERVICE WORKSHEET11/14/19